Time limit: 2.0s Memory limit: 256M

Canadian Computing Competition: 2010 Stage 1, Senior #2

There is an ingenious text-compression algorithm called *Huffman coding*, designed by David Huffman in 1952.

The basic idea is that each character is associated with a binary sequence (i.e., a sequence of @ s and 1 s). These binary sequences satisfy the *prefix-free property*: a binary sequence for one character is never a prefix of another character's binary sequence.

It is worth noting that to construct a prefix-free binary sequence, simply put the characters as the leaves of a binary tree, and label the "left" edge as @ and the "right" edge as 1. The path from the root to a leaf node forms the code for the character at that leaf node. For example, the following binary tree constructs a prefix-free binary sequence for the characters $\{A, B, C, D, E\}$:



That is, A is encoded as 00, B is encoded as 01, C is encoded as 10, D is encoded as 110 and E is encoded as 111.

The benefit of a set of codes having the prefix-free property is that any sequence of these codes can be uniquely decoded into the original characters.

Your task is to read a Huffman code (i.e., a set of characters and associated binary sequences) along with a binary sequence, and decode the binary sequence to its character representation.

Input Specification

The first line of input will be an integer k ($1 \le k \le 20$), representing the number of characters and associated codes. The next k lines each contain a single character, followed by a space, followed by the binary sequence (of length at most 20) representing the associated code of that character. You may assume that the character is an alphabet character (i.e., $a \ldots z$ and $A \ldots Z$). You may assume that the sequence of binary codes has the prefix-free property. On the k + 2nd line is the binary sequence which is to be decoded. You may assume the binary sequence contains codes associated with the given characters, and that the k + 2nd line contains no more than 250 binary digits.

Output Specification

On one line, output the characters that correspond to the given binary sequence.

Sample Input

5			
A 00			
B 01			
C 10			
D 110			
E 111			
00000101111			

Output for Sample Input

AABBE