

# IOI '99 P4 - Traffic Lights

---

**Time limit:** 1.0s    **Memory limit:** 16M

---

## IOI '99 - Antalya-Belek, Turkey

In the city of Dingilville the traffic is arranged in an unusual way. There are junctions and roads connecting the junctions. There is at most one road between any two different junctions. There is no road connecting a junction to itself. Travel time for a road is the same for both directions. At every junction there is a single traffic light that is either blue or purple at any moment. The color of each light alternates periodically: blue for certain duration and then purple for another duration. Traffic is permitted to travel down the road between any two junctions, if and only if the lights at both junctions are the same color at the moment of departing from one junction for the other. If a vehicle arrives at a junction just at the moment the lights switch it must consider the new colors of lights. Vehicles are allowed to wait at the junctions. You are given the city map which shows

- the travel times for all roads (integers),
- the durations of the two colors at each junction (integers)
- and the initial color of the light and the remaining time (integer) for this color to change at each junction.

Your task is to find a path which takes the minimum time from a given source junction to a given destination junction for a vehicle when the traffic starts. In case more than one such path exists you are required to report only one of them.

## Input Specification

---

The first line contains two numbers: The id-number of the source junction and the id-number of the destination junction. The second line contains two numbers: the number of junctions  $N$  ( $2 \leq N \leq 300$ ) and the number of roads  $M$  ( $1 \leq M \leq 14\,000$ ). The following  $N$  lines contain information on  $N$  junctions. The  $(i + 2)^{\text{th}}$  line of the input file holds information about the junction  $i$ :

- the initial color  $C_i$  (either **B** or **P**)
- the remaining time for the initial color  $c$ ,  $r_{ic}$  ( $1 \leq r_{ic} \leq t_{ic}$ )
- the length of time for which the junction stays blue,  $t_{iB}$  ( $1 \leq t_{iB} \leq 100$ )
- the length of time for which the junction stays purple,  $t_{iP}$  ( $1 \leq t_{iP} \leq 100$ )

Finally, the next  $M$  lines contain information on  $M$  roads. Each line is of the form:  $i, j, l_{ij}$  ( $1 \leq l_{ij} \leq 100$ ) where  $i$  and  $j$  are the id-numbers of the junctions which are connected by this road and  $l_{ij}$  is the time required to move along this road.

## Output Specification

---

If a **path exists**:

- The first line will contain the time taken by a minimum-time path from the source junction to the destination junction.
- Second line will contain the list of junctions that construct the minimum-time path you have found. You have to write the junctions to the output file in the order of travelling. Therefore the first integer in this line must be the id-number of the source junction and the last one the id-number of the destination junction.

If a **path does not exist**:

- A single line containing only the integer `0`.

## Sample Input

---

```
1 4
4 5
B 2 16 99
P 6 32 13
P 2 87 4
P 38 96 49
1 2 4
1 3 40
2 3 75
2 4 76
3 4 77
```

## Sample Output

---

```
127
1 2 4
```